

## 平面塗佈機

# Patch Coater

適用基板尺寸  
G3: 550x650mm

Coating for rigid substrate  
Size: 550x650

### •塗佈平台

- 精密等級花崗岩平台
- 基板防撞偵測
- 基材頂針機構

### Coating station

- High precision table made of granite
- With anti-collision mechanism
- With lifter mechanisz

### •傳動方式：

水平採用氣浮平台設計，以空氣軸承搭配無剛性馬達，可穩定動作，無磨耗  
垂直採用線軌搭配滾珠螺桿，雙軸同動，重複可再現精度2um內

Horizontal movement by air lifter for high smooth and stable movement without wear-out issue.

Vertical movement by ball screw with linear rail for high repeatability within 2um.

### •唇口自潔機構

- 搭配唇口刮刀機構確保上膠前唇口清潔
- 搭配溶劑噴嘴清潔刮刀

### Nozzle lip cleane

- With lip scraper to quarantee lip cleanness before coating
- Solvent spray to clean scraper



## 平面塗佈機 Patch Coater (Size A4)


適用小批次原料及樣品打樣開發  
含抽真空VCD設計

Apply for sample or batch demand.

With vacuum chamber design for solvent degassing.



Substrate	Glass, Plastic Sheet/Film or Copper/Aluminum Foil
Size	A4(210mmX300mm)
Speed Control	10~200 mm/sec, By digital setting.
Coating Path	Step-less setting from start to end.
Coating Width	Max. 210mm
Power Supply	220V/60HZ
PLC Control	Electronic Control



**GMA** 政鈺機械股份有限公司  
GMA MACHINERY ENTERPRISE CO., LTD.



📍 43547台中市梧棲區永興路二段362巷28號 | No.28 Lane 362, Sec. 2, Yung Hsing Rd., Wu Chi Dist., Taichung

☎ +886-4-26303228

✉ info@gma.com.tw

☎ +886-4-26303208

🌐 www.gmatw.com